



Bonded tubing provides a no tangle alternative to stringing individual lines. Saves up to 60% space. Bonded rows are color coded for easy identification. Lots are laser marked for full traceability - customization available.

SPECIFICATIONS

Virgin Polyether PU Material - UV Stabilized
 Fluid Type: Compressed Air, Water
 Hardness: 95A Shore
 Operating Pressure: -14 ~ +116 PSI (-1 ~ 8 bar)
 Operating Temperature: -20°C ~ +60°C
 Peak Temperature: +70°C (short duration)
 Bend Radius (Flow): 1" (26 mm)
 Minimum Bend Radius: 0.6" (15 mm)
 Abrasion Resistance: Excellent
 Hydrolysis Resistance: High (Polyether)
 Chemical Resistance: Good against oils, greases, & solvents
 Compliance & Certifications

- RoHS Compliant
- REACH Compliant
- ISO 9001 Manufacturing
- CE
- FDA Food-Grade Option Available

ORDER CODE

MC

MULTIPLE
CHANNEL
PU

8X6

Tube Dia

3

Length

BK

Color
White
Black
Yellow
Clear
Red

Code
WH
BK
YL
TR
RD

APPLICATION



STANDARD SIZES

MULTIPLE ROWS TUBE							
Item No.	Rize Size			Row number			
	Cuter O.D	Inner I.D	Length				
	mm	mm	M				
PU 6*4	6	4	100	2	3	4	6
PU 8*5	6	5	100	2	3	4	6
PU 10*6.5	10	6.5	50	2	3	4	6

CUSTOMIZATION AVAILABLE TO SUIT YOUR NEEDS